

FIREBOX T45

Available with optional integrated Wi-Fi 6 wireless module Up to 3.94 Gbps firewall throughput, 5 x 1Gb ports, 30 Branch Office VPNs



DATASHEET

ENTERPRISE-GRADE SECURITY FOR BRANCH OFFICES AND RETAIL ENVIRONMENTS

WatchGuard Firebox T45 tabletop appliances bring enterprise-level network security to small office/branch office and retail environments. These appliances are small-footprint, cost-effective security powerhouses that deliver all the features present in WatchGuard's higher-end UTM appliances, including all security capabilities, such as Al-powered anti-malware, threat correlation, and DNS-filtering.

"We are deeply impressed by the outstanding performance of this tabletop device. This device, having one PoE+ port for powering a phone or access point, is an excellent choice for connecting home offices or smaller branch offices."

~ Bernd Och, CEO, BOC IT-Security GmbH

BIG SECURITY IN A SMALL APPLIANCE

With the Total Security Suite, WatchGuard's Firebox includes a complete and industry-best set of threat management solutions, including gateway antivirus, content and URL filtering, antispam, intrusion prevention, application control, Cloud sandboxing, and endpoint protections, all in an easy-to-manage package.

QUICK AND SIMPLE DEPLOYMENT

Zero-touch deployment makes it possible to eliminate much of the labor involved in setting up a Firebox to connect to your network - all without having to leave your office. A robust, Cloud-based deployment and configuration tool comes standard with WatchGuard Firebox appliances. Local staff connects the device to power and the Internet, and the appliance connects to the Cloud for all its configuration settings.

Integrated support for PoE+ means you can avoid running separate power cables to peripheral devices like security cameras, VoIP phones, or wireless access points.

UNIFIED SECURITY PLATFORM® ARCHITECTURE

WatchGuard's Unified Security Platform framework is built from the ground up to enable a single console solution for provisioning, deploying, managing, and monitoring an integrated portfolio of advanced cybersecurity solutions and services. This comprehensive portfolio of endpoint, multi-factor authentication, Wi-Fi, and network security solutions (including Firebox firewall appliances) helps stop the attempted discovery and exploitation of vulnerable systems, phishing, ransomware, intrusions, and advanced malware across all users, environments, and devices. Our Unified Security Platform architecture replaces the old patchwork security approach and makes it possible to extend security capabilities to every computing environment where your business operates.

NETWORK OPTIMIZATION WITH SD-WAN

Firebox T45 makes network optimization easy. With integrated SD-WAN, you can decrease your use of expensive MPLS or cellular connections and inspect traffic from small offices while improving the resiliency and performance of your network.

FEATURES & BENEFITS

- 5 Gigabit Ethernet ports support high-speed LAN backbone infrastructures & gigabit WAN connections.
- Integrated PoE+ port for powering peripheral devices.
- Wi-Fi capable Firebox T45-W-PoE supports the 802.11ax Wi-Fi 6 standard, ensuring fast speeds for your users.
- All logging and reporting functions included with purchase, with over 100 dashboards and reports including PCI and HIPAA.

FIREBOX T45

Firebox T45 /T45-PoE /T45-W-PoE

/14J-FUL/14J-W-FUL	TECHNICAL SPECIFICATIONS		
THROUGHPUT ¹			
UTM (full scan) ²	557 Mbps		
Firewall (IMIX)	1.44 Gbps		
VPN (IMIX)	460 Mbps		
HTTPS Content Inspection (IPS enabled) ³	301 Mbps		
Antivirus	874 Mbps		
IPS (full scan)	716 Mbps		
Firewall (UDP 1518)	3.94 Gbps		
VPN (UDP 1518)	1.58 Gbps		
CAPACITY			
Interfaces 10/100/1000	5		
I/O interfaces	1 Serial/2 USB		
Concurrent connections	3,850,000		
Concurrent connections (Proxy)	3,850,000		
New connections per second	26,500		
VLANs	50		
WSM licenses (incl)	0		
TDR Host Sensors included	20		
VPN TUNNELS			
Branch Office VPN	30		
Mobile VPN	30		
SECURITY FEATURES			
Firewall	Stateful packet inspection, TLS decryption, proxy firewall		
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3S, SMTPS, IMAPS and Explicit Proxy		
Threat protection	DoS attacks, fragmented & malformed packets, blended threats		
Filtering options	Browser Safe Search, Google for Business		
VPN			
Site to Site VPN	IKEv2, IPSec, Policy and Route Based Tunnels, TLS hub and spoke		
Remote Access VPN	IKEv2, IPSec, L2TP, TLS		
VISIBILITY			
Logging and notifications	WatchGuard Cloud & Dimension, Syslog, SNMP v2/v3		
Reporting	WatchGuard Cloud includes over 100 pre-defined reports, executive summary and visibility tools		
CERTIFICATIONS			
Security	Pending: CC, FIPS 140-2		
Safety	NRTL/CB		
Network	IPv6 Ready Gold (routing)		
Hazardous substance control	WEEE, RoHS, REACH		
NETWORKING			
SD-WAN	Multi-WAN failover, dynamic path selection, jitter/loss/latency measurement		
Dynamic Routing	RIP, OSPF, BGP		
High Availability	Active/passive, active/active		
QoS	802.1Q, DSCP, IP Precedence		
Traffic Management	By policy or application		
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS		
NAT	Static, dynamic, 1:1, IPSec traversal, policy-based		
Link aggregation	802.3ad dynamic, static, active/backup		

TECHNICAL SPECIFICATIONS

¹ Throughput rates are determined using multiple flows through multiple ports and will vary depending on environment and configuration. Max firewall throughput tested via direct connection using 1518 byte UDP frame based on RFC 2544 methodology. All testing performed on Fireware version 12.6.

 $^{\rm 2}$ UTM throughput is measured using HTTP traffic with AV, IPS, and Application Control enabled, and does not account for all security services available on the appliance.

³ HTTPS throughput is measured per NetSecOPEN methodology - 256k response with TLS1.2 AES256 + SHA-256.

LEDS

PHYSICAL AND POWER SPECIFICATIONS					
Product Dimensions (W x D x H)		8" x 8.5" x 1.7" (203.2 mm x 215.9 mm x 43.2 mm)			
Product Weight		T45/T45-PoE: 1.94 T45-W-PoE: 1.98 lb			
Shipping Dimensions (W x D x H)		12.1" x 10.2" x 7.2" (308 mm x 261 mm x 181 mm)			
Shipping Weight		4.1 lbs (1.86 kg)			
Power		100-240 VAC Autosensing			
Power Consumption		No PoE: 24 Watts With PoE: 60 Watts			
MTBF		157,751 hours			
ENVIRONMENT	OPERATING		STORAGE		
Temperature	32 °F to 104 °F (0 °C to 40 °C)		-40 °F to 158 °F (-40 °C to 70 °C)		
Relative Humidity	10% to 85% non-condensing		10% to 85% non-condensing		
Altitude		3 ft at 95 °F 0 m at 35 °C)	0 to 15,000 ft at 95 °F (0 to 4,570 m at 35 °C)		

STRONG SECURITY AT EVERY LAYER

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, phishing and much more. Total and Basic Security Suite packages are available on all Firebox solutions.

	SUPPORT	BASIC SECURITY	TOTAL SECURITY
Stateful Firewall	1	1	1
VPN	1	\checkmark	1
SD-WAN	\checkmark	\checkmark	1
Access Portal*	\checkmark	\checkmark	1
Intrusion Prevention Service (IPS)		\checkmark	1
Application Control		\checkmark	1
WebBlocker		\checkmark	1
spamBlocker		\checkmark	1
Gateway AntiVirus		\checkmark	1
Reputation Enabled Defense		\checkmark	1
Network Discovery		\checkmark	1
APT Blocker			1
DNSWatch			1
IntelligentAV**			1
ThreatSync (XDR)			1
EDR Core			20
WatchGuard Cloud Visibility Data Retention		1 Day	30 Days
Support	Standard (24 x 7)	Standard (24 x 7)	Gold (24 x 7)

For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

* Not available on Firebox T20/T20-W, T25/T25-W, or T35-R. Total Security Suite required for M270, M370, M470, M570, M670, FireboxV and Firebox Cloud.
** Not available on Firebox T20/T20-W, T25/T25-W, or T35-R.

Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. Visit www.watchguard.com/sizing to access the online Product Sizing Tool.

U.S. SALES +1.800.734.9905 INTERNATIONAL SALES +1.206.613.0895 WEB www.watchguard.com

No express or implied warranties are provided for herein. All specifications are subject to change and expected future products, features or functionality will be provided on an if and when available basis. ©2023 WatchGuard Technologies, Inc. All rights reserved. WatchGuard, the WatchGuard logo, Firebox, DNSWatch, IntelligentAV and Unified Security Platform are trademarks or registered trademarks of WatchGuard Technologies, Inc. in the United States and/or other countries. All other tradenames are the property of their respective owners. Part No. WGCE67649_021523